



www.task-es.com

OFM-SERIES

MUDCOOLER

OFFSHORE MUDCOOLER

- **Extremely suitable for HP/HT drilling**
- **Different versions to suit individual cooling and environmental needs**
- **Extends service life of drilling equipment**
- **Improves working conditions**
- **Patented system to protect the environment**

Task Environmental Services
Worldwide BV
Magelhaenstraat 16
7825 VK Emmen
The Netherlands

T +31(0)591-210220
F +31(0)591-210221
E info@task-es.com
I www.task-es.com

We get the task done!

OFFSHORE MUDCOOLER

Offshore mudcoolers need to comply with specific requirements. Apart from robust and compact construction, they sometimes must be able to meet strict environmental standards set by authorities. Task has developed a range of offshore mudcoolers that will meet any demand. They all share a modular design, which allows them to be easily adapted or built to your specifications

The OFM-D series mudcoolers feature a direct cooling system using sea water for cooling. For higher cooling demands, it can be equipped with a tandem cooling unit, in which the second unit functions in parallel to the first unit. You can choose the capacity to suit your needs and still be ensured of the quality and reliability of Task's equipment.

When environmental protection is of key importance, you can choose to install a mudcooler from Task's OFM-I series. All Task's OFM-I series mudcoolers feature a patented closed circuit cooling system with oil detection. Oil leakage problems are excluded, allowing you to perform your drilling operations within the strictest environmental regulations and observing maximum environmental protection.

Task can build your mud cooling equipment according to your specifications. In these cases our modular design practices and wide experience in the field of offshore equipment technology will ensure short delivery times and problem free commissioning of your equipment. Clever tool design and modern production facilities ensure that all materials are processed for maximum safety and durability, extending the service life of your drilling equipment and improving working conditions on your platform.



Technical Details

Model		OFM-DS 4000	OFM-DT 4000	OFM-IS 2000	OFM-IS 3000	OFM-IS 4000
Dimensions						
Length	mm	3000	3000	4400	4500	4550
Width	mm	2000	2000	1400	2000	2000
Height (total)	mm	2500	2500	2000	2000	2000
Weight (total)	kg	4000	5000	4500	6000	6500
Cooler Specs						
Flowrate	ltr/min	2500	2500	2500	2500	2500
Mud Density	kg/ltr	1,85	1,85	1,85	1,85	1,85
Design Inlet Temperature	°C	85	85	85	85	85
Design Outlet Temperature	°C	50	50	65	60	50
Seawater Temperature	°C	15	15	15	15	15
Cooling Capacity	kW	4000	4000	2000	3000	4000

